1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

3-POLE SOFT WIRING — POWER OUTLETS

Double GPO Quick Fit Outlet

QF-2GPO







This Quick Fit outlet puts two GPOs in one compact module that snaps straight into Quick Fit compatible power rails, table boxes and floor boxes, with no tools. All sockets are auto-switched and rated 10A 250V; 20A GST connectors suit low-profile, re-wireable Wieland GST cabling, and male and female connectors allow modules to be daisy-chained.

TECHNICAL SPECIFICATIONS

Outlets	**2 x GPO**
Connection	**Wieland (GST) soft wiring connector, no lead**
Mounting	**Quick Fit modular snap-in**
Colours	**Black, white or red**
Socket Rating	**10A 250V, auto-switched**
Connectors	**20A GST (Wieland), male and female for daisy-chaining**
Panel Cut-Out	**130.5 × 41.5mm, panels up to 3mm (3–14mm with thick panel frame)**
Approval	**NSW 23497; connectors to IEC 61535 and AS/NZS 61535**

DIMENSIONS

All dimensions nominal (mm)

PANEL CUT-OUT	PANEL THICKNESS
130.5×41.5 mm	**≤3** mm

KEY FEATURES

- 2 x auto-switched GPO in one compact Quick Fit module
- Snaps into Quick Fit compatible power rails, table boxes and floor boxes, no tools
- Sockets rated 10A 250V
- 20A GST (Wieland) connectors allow modules to be daisy-chained
- Fits industry-standard 130.5 × 41.5mm cut-outs in panels up to 3mm
- Black, white or red
- 3 part numbers to choose from

TYPICAL APPLICATIONS

Workstations	Meeting rooms
Retail	Commercial fitouts
Education	

ORDERING INFORMATION

Black	**152100**
Red	**152102**
White	**152104**
Warranty	**Manufacturer's warranty**