1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

3-POLE SOFT WIRING — POWER OUTLETS

Quad GPO Quick Fit Outlet, Removable Tile

QF-4GPO







This Quick Fit quad outlet has a removable fascia tile, so one socket position can later be swapped for a Quick Fit USB charging module without replacing the unit. All sockets are auto-switched and rated 10A 250V, with multi-directional sockets and 20A GST (Wieland) connectors for daisy-chaining.

TECHNICAL SPECIFICATIONS

Outlets	**4 x GPO, removable tile**
Connection	**Wieland (GST) soft wiring connector, no lead**
Mounting	**Quick Fit modular snap-in**
Upgrade	**Accepts the Quick Fit USB charging module**
Colours	**Black or white**
Socket Rating	**10A 250V, auto-switched, multi-directional**
Connectors	**20A GST (Wieland), male and female for daisy-chaining**
Panel Cut-Out	**230.5 × 41.5mm, panels up to 3mm (3–14mm with thick panel frame)**
Approval	**NSW 23497; connectors to IEC 61535 and AS/NZS 61535**

DIMENSIONS

All dimensions nominal (mm)	
PANEL CUT-OUT **230.5×41.5** mm	PANEL THICKNESS **≤3** mm

KEY FEATURES

- 4 x auto-switched, multi-directional GPO
- Removable fascia tile: swap one socket position for a Quick Fit USB module later
- Sockets rated 10A 250V
- 20A GST (Wieland) connectors allow modules to be daisy-chained
- Fits industry-standard 230.5 × 41.5mm cut-outs in panels up to 3mm
- Black or white
- 2 part numbers to choose from

TYPICAL APPLICATIONS

Office fit-outs	Workstation soft wiring
Modular power distribution	

ORDERING INFORMATION

Black	**152276**
White	**152277**
Warranty	**Manufacturer's warranty**