1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

3-POLE SOFT WIRING — INTERCONNECT LEADS

3-Pole Soft Wiring Interconnect Lead

SW-IL







Interconnect leads link the parts of a soft wiring system together: starters, distribution blocks, power units and outlets.

TECHNICAL SPECIFICATIONS

Connectors	**20A snap connectors, male and female**
Poles	**3**
Rating	**20A**
Locking	**Positive locking clip, clicks when fully engaged**
Lengths	**300mm, 600mm, 1000mm to 10000mm in 500mm steps**
Colours	**Black or white**
Standard	**AS/NZS 61535**

KEY FEATURES

- Each lead has a male and a female 20A snap connector with a positive locking clip that clicks when fully engaged.
- Connectors: 20A snap connectors, male and female
- Poles: 3
- Rating: 20A
- Available in Black, White
- 32 part numbers to choose from (full list on page 2)

TYPICAL APPLICATIONS

Office fit-outs	Workstation soft wiring
Modular power distribution	

ORDERING INFORMATION

Product Family	**SW-IL**
Part Numbers	**32 options, listed in full on page 2**
Warranty	**Manufacturer's warranty**

1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

3-Pole Soft Wiring Interconnect Lead — Part Numbers

SW-IL

All 32 part numbers in the SW-IL family, as listed on cableduct.com.au.

PART NUMBERS

Part Number	Colour	Cable Length
150094	Black	300mm
150046	Black	600mm
150003	Black	1000mm
150005	Black	1500mm
150007	Black	2000mm
150009	Black	2500mm
150011	Black	3000mm
150013	Black	3500mm
150015	Black	4000mm
150017	Black	4500mm
150019	Black	5000mm
150021	Black	6000mm
150023	Black	7000mm
150025	Black	8000mm
150027	Black	9000mm
150029	Black	10000mm
142000	White	300mm
150049	White	600mm
150004	White	1000mm
150006	White	1500mm
150008	White	2000mm
150010	White	2500mm
150012	White	3000mm
150014	White	3500mm
150016	White	4000mm
150018	White	4500mm
150020	White	5000mm
150022	White	6000mm
150024	White	7000mm
150026	White	8000mm
150028	White	9000mm
150030	White	10000mm

For quotes, stock and technical assistance email sales@cableduct.com.au or call 1300 302 249.