1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

3-POLE SOFT WIRING — SOFTWIRE STARTERS

3-Pole Soft Wire Starter Cable, Thermal Overload

SWTOC







The thermal overload starter cable powers a soft wiring run from a standard wall outlet, with no hard-wiring needed.

TECHNICAL SPECIFICATIONS

Plug	**AS/NZS 3-pin AU plug**
Protection	**In-line thermal overload near the plug**
Connector	**3-pole soft wiring connector**
Rating	**10A**
Lengths	**1.8m, 2.0m, 5.0m**
Colours	**White or black**

KEY FEATURES

- The in-line thermal overload near the plug protects the circuit against overload.
- Plug: AS/NZS 3-pin AU plug
- Protection: In-line thermal overload near the plug
- Connector: 3-pole soft wiring connector
- Available in Black, White
- 4 part numbers to choose from

TYPICAL APPLICATIONS

Office fit-outs	Workstation soft wiring
Modular power distribution	

ORDERING INFORMATION

Black · 1800mm	**SWTOC1.8M-BK**
Black · 5000mm	**SWTOC5.0M-BK**
White · 2000mm	**SWTOC2.0M-WH**
White · 5000mm	**SWTOC5.0M-WH**
Warranty	**Manufacturer's warranty**