1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — BRASS LID FLOOR BOXES

Brass Tile Recessed Floor Box, 1 x Double GPO

FOBBR19R1STDO









The FOBBR19R1STDO recessed lid floor box features a 19mm Brass hinged lid, a Steel box body, and 1 x Standard DGPO Outlet provision. Previously known as FFOB-149B/2P.

TECHNICAL SPECIFICATIONS

Part Number	**FOBBR19R1STDO**
Series	**FOBBR19R1STDO Recessed Lid Floor Box**
Lid Material	**Brass Hinged Lid, 19mm Recessed**
Body Material	**Steel**
Outlet Configuration	**1 x Standard DGPO Outlet**
Conduit Entry	**5 x 25mm Knockouts (4 side, 1 base)**
Weight	**2.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 146×155×101 mm · dimensions nominal

BOX BODY
126×135×67 mm

SLAB BLOCK-OUT
146×155×101 mm

RAISED FLOOR CUT-OUT
128×137 mm

KEY FEATURES

- Brass hinged lid, 19mm rebate, suits floor finish
- Cord exit flap with dust guards and recessed handle
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 126 x 135 x 67mm nominal depth
- 5 x 25mm conduit knockouts (4 on the side of the box, 1 on the base)
- 1 x Standard DGPO Outlet provision

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBBR19R1STDO**
Series	**FOBBR19R1STDO Recessed Lid Floor Box, Brass, 1 x Standard DGPO Outlet**
Block-out in Concrete Slab	**146 x 155 x 101mm nominal**
Warranty	**Manufacturer's warranty**