1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — BRASS LID FLOOR BOXES

Brass Flush Floor Box, Double GPO + 3 x Data

FOBBRF1STDO3D









The FOBBRF1STDO3D flush lid floor box features a Brass hinged lid, a Steel box body, and a bracket for 1 x Clipsal 2000 Series Power/Data/AV outlet with 3-gang data provision. Previously known as FFOB-147.

TECHNICAL SPECIFICATIONS

Part Number	**FOBBRF1STDO3D**
Series	**FOBBRF1STDO3D Flush Lid Floor Box**
Lid Material	**Brass Hinged Lid (145 x 145mm)**
Body Material	**Steel**
Outlet Configuration	**1 x Clipsal 2000 Series Outlet Bracket + 3-Gang Data Provision**
Conduit Entry	**10 x 25mm Knockouts (2 each side, 2 base)**
Weight	**2.2 kg (approx.)**

DIMENSIONS

Block-out in slab: 146×155×110 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
126×135×100 mm	**146×155×110** mm
RAISED FLOOR CUT-OUT	
128×137 mm	

KEY FEATURES

- Brass hinged lid (145 x 145mm) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 126 x 135 x 100mm nominal depth
- 10 x 25mm conduit knockouts (2 on each side, 2 on the base)
- Outlet bracket to suit 1 x Clipsal 2000 Series style Power/Data/AV outlet
- 1 x 3-gang data outlet clip supplied
- Floating floor brackets available upon request

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBBRF1STDO3D**
Series	**FOBBRF1STDO3D Flush Lid Floor Box, Brass, Clipsal 2000 Series Outlet + 3-Gang Data**
Block-out in Concrete Slab	**146 x 155 x 110mm nominal**
Warranty	**Manufacturer's warranty**