
1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — BRASS LID FLOOR BOXES


Brass Recessed Floor Box, 4 x Auto-Switched GPO + 5 x Data

FOBBRR4P5DS80









The FOBBRR4P5DS80 recessed lid floor box features a hinged Brass lid with a 14mm recessed tile/carpet insert pocket, a shallow-depth Steel box body, and 4 x 10Amp Round Auto Switched GPOs plus 5 x Single Data Outlet Clips for power and data connectivity. Previously known as FFOB-248B/80.

TECHNICAL SPECIFICATIONS

Part Number	**FOBBRR4P5DS80**
Series	**FOBBRR4P5DS80 Recessed Lid Floor Box**
Lid Material	**Brass, Hinged, 14mm Recessed (Tile/Carpet Insert)**
Body Material	**Steel**
Outlet Configuration	**4 x 10Amp Round Auto Switched GPOs + 5 x Single Data Outlet Clips**
Conduit Entry	**8 x Combination 25/32mm Knockouts (4 side, 4 base)**
Weight	**5.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 250×247×89 mm · dimensions nominal

LID SIZE **245×245** mm	BOX BODY **230×227×79** mm
SLAB BLOCK-OUT **250×247×89** mm	RAISED FLOOR CUT-OUT **232×229** mm

KEY FEATURES

- Hinged Brass lid (245 x 245mm) with 14mm recessed pocket for tile or carpet insert, screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 230 x 227 x 79mm nominal depth (shallow 80mm carcass)
- 8 x combination 25/32mm conduit knockouts (4 side, 4 base)
- 4 x 10Amp Round Auto Switched GPOs (supplied)
- 5 x Single Data Outlet Clips (supplied)

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBBRR4P5DS80**
Series	**FOBBRR4P5DS80 Recessed Lid Floor Box (Brass, 14mm Recessed, 4 x GPO + 5 x Data, Shallow 80mm)**
Block-out in Concrete Slab	**250 x 247 x 89mm nominal**
Warranty	**Manufacturer's warranty**