
1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — IP RATED FLOOR BOXES

IP66 Stainless Steel Floor Box, Flush Finish, 2 x Data, Allen Key Lock

FOBSS2D-IP66AK





The FOBSS2D-IP66AK is an IP66 rated in-floor outlet box with a stainless steel flush lid, holding 2 x Data Outlets. Designed for installation in a poured concrete slab, it uses a fireproof thermoplastic box body with an MDF temporary lid that protects the unit from concrete slurry during the pour, and is fitted with a Allen key lock.

TECHNICAL SPECIFICATIONS

Component	**In-Floor Outlet Box**
Lid Material	**Stainless Steel**
Outlet Configuration	**2 x Data Outlets**
Mechanism Holding Unit	**130mm x 130mm**
Box Body	**Fireproof thermoplastic, 135mm x 135mm x 69mm nom. deep**
Concrete Block-Out (Cut-Out)	**155mm x 155mm x 79mm nom.**
Lid Lock	**Allen key locking system**
Ingress Protection (typical for this class)	**IP66 closed / IP20 in use**
Load Rating (typical for this class)	**Up to 1000kg closed / 170kg open**

DIMENSIONS

Block-out in slab: 155×155×79 mm · dimensions nominal

MECHANISM UNIT	BOX BODY
130×130 mm	**135×135×69** mm
SLAB BLOCK-OUT	
155×155×79 mm	

KEY FEATURES

- IP66 rated: IP66 closed / IP20 in use
- Stainless Steel flush lid
- 2 x Data Outlets
- Box body: Fireproof thermoplastic, 135mm x 135mm x 69mm nom. deep
- MDF temporary lid protects the box from concrete slurry during the pour
- Allen key locking system
- Load rating: Up to 1000kg closed / 170kg open

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSS2D-IP66AK**
Description	**IP66 Stainless Steel Floor Box, Flush Finish, 2 x Data, Allen Key Lock**
Warranty	**Manufacturer's warranty**