1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES

Stainless Steel Round Flush Floor Box, 1 x Double GPO

FOBCSSF1STDO









The FOBCSSF1STDO flush lid floor box features a Round Stainless Steel hinged lid, a Steel box body, and 1 x Standard Double GPO Outlet. Previously known as FFOB-145R.

TECHNICAL SPECIFICATIONS

Part Number	**FOBCSSF1STDO**
Series	**FOBCSSF1STDO Floor Box 1 Standard DGPO**
Lid Material	**Round Stainless Steel Hinged Lid (145 x 145mm)**
Body Material	**Steel**
Outlet Configuration	**1 x Standard Double GPO (10Amp)**
Conduit Entry	**5 x 25mm Knockouts (4 side, 1 base)**
Weight	**2.1 kg (approx.)**

DIMENSIONS

Block-out in slab: 146×155×110 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
126×135×100 mm	**146×155×110** mm
RAISED FLOOR CUT-OUT	
128×137 mm	

KEY FEATURES

- Round stainless steel hinged lid (145 x 145mm) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 126 x 135 x 100mm nominal depth
- 5 x 25mm conduit knockouts (4 on the side of the box, 1 on the base)
- 1 x Standard Double GPO outlet
- Floating floor brackets available upon request

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBCSSF1STDO**
Series	**FOBCSSF1STDO Floor Box 1 Standard DGPO, Round Stainless Steel**
Block-out in Concrete Slab	**146 x 155 x 110mm nominal**
Warranty	**Manufacturer's warranty**