1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES

Stainless Steel Tile Recessed Floor Box, Double GPO + 3 x Data

FOBSS19R1STDO3D









The FOBSS19R1STDO3D recessed lid floor box features a 19mm Stainless Steel recessed lid, a Steel box body, and 1 x Double GPO Outlet plus 3 x Data Provisions. Previously known as FFOB-149/2P3D.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSS19R1STDO3D**
Series	**FOBSS19R1STDO3D Recessed Lid Floor Box**
Lid Material	**Stainless Steel, 19mm Recessed**
Body Material	**Steel**
Outlet Configuration	**1 x Double GPO Outlet + 3 x Data Provisions**
Conduit Entry	**5 x 25mm Knockouts (4 side, 1 base)**
Weight	**2.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 146×155×101 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
126×135×100 mm	**146×155×101** mm
RAISED FLOOR CUT-OUT	
128×137 mm	

KEY FEATURES

- Stainless Steel recessed lid (19mm rebate) sits flush with the floor finish
- Cord exit flap with dust guards and recessed handle allows cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 126 x 135 x 100mm nominal depth
- 5 x 25mm conduit knockouts (4 on the side of the box, 1 on the base)
- 1 x Double GPO Outlet
- 3 x Data Provisions

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSS19R1STDO3D**
Series	**FOBSS19R1STDO3D Recessed Lid Floor Box, Stainless Steel, 1 x Double GPO + 3 x Data**
Block-out in Concrete Slab	**146 x 155 x 101mm nominal**
Warranty	**Manufacturer's warranty**