
1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES

Stainless Steel Square Edge Flush Floor Box, Double GPO + 3 x Data

FOBSSF1STDO3D-SE





The FOBSSF1STDO3D-SE flush lid floor box features a hinged Stainless Steel lid, a Steel box body, and 1 x Double GPO Outlet plus 3 x Data Provisions for reliable power and data connectivity. Previously known as FFOB-148F.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSF1STDO3D-SE**
Series	**FOBSSF1STDO3D-SE Flush Lid Floor Box**
Lid Material	**Stainless Steel, Hinged**
Body Material	**Steel**
Outlet Configuration	**1 x Double GPO Outlet + 3 x Data Provisions**
Conduit Entry	**10 x 25mm Conduit Knockouts (8 side, 2 base)**
Weight	**2.2 kg (approx.)**

DIMENSIONS

Block-out in slab: 146×155×110 mm · dimensions nominal

LID SIZE	BOX BODY
145×145 mm	**126×135×100** mm
SLAB BLOCK-OUT	RAISED FLOOR CUT-OUT
146×155×110 mm	**128×137** mm

KEY FEATURES

- Hinged Stainless Steel lid (145 x 145mm) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 126 x 135 x 100mm nominal depth
- 10 x 25mm conduit knockouts (8 side, 2 base)
- 1 x 3-Gang Data Outlet Clip (supplied)
- Floating floor brackets available upon request

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSSF1STDO3D-SE**
Series	**FOBSSF1STDO3D-SE Flush Lid Floor Box (Stainless Steel, 1 x Double GPO + 3 Data)**
Block-out in Concrete Slab	**146 x 155 x 110mm nominal**
Warranty	**Manufacturer's warranty**