1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES


Stainless Steel Flush Floor Box, Quad GPO + 12 x Data

FOBSSF3STDO









The FOBSSF3STDO flush lid floor box features a hinged Stainless Steel lid, a Steel box body, and an outlet bracket configured to suit 1 x Quad GPO (or Dual GPO) with up to 12 x Data. Previously known as FFOB-245.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSF3STDO**
Series	**FOBSSF3STDO Flush Lid Floor Box**
Lid Material	**Stainless Steel, Hinged**
Body Material	**Steel**
Outlet Configuration	**1 x Quad GPO (or Dual GPO) + Up to 12 x Data**
Conduit Entry	**13 x Combination 25/32mm Knockouts (10 side, 3 base)**
Weight	**5.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 248×247×120 mm · dimensions nominal

LID SIZE	BOX BODY
245×245 mm	**228×227×110** mm
SLAB BLOCK-OUT	RAISED FLOOR CUT-OUT
248×247×120 mm	**230×229** mm

KEY FEATURES

- Hinged Stainless Steel lid (245 x 245mm) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 228 x 227 x 110mm nominal depth
- 13 x combination 25mm/32mm conduit knockouts (10 side, 3 base)
- Outlet bracket to suit 1 x Quad GPO (or Dual GPO) & up to 12 x Data

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSSF3STDO**
Series	**FOBSSF3STDO Flush Lid Floor Box (Stainless Steel, 1 x Quad GPO + 12 Data)**
Block-out in Concrete Slab	**248 x 247 x 120mm nominal**
Warranty	**Manufacturer's warranty**