1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES


Stainless Steel Square Edge Flush Floor Box, 4 x Auto-Switched GPO + 5 x Data

FOBSSF4P5DS80-SE









The FOBSSF4P5DS80-SE flush lid floor box features a hinged, square edge Stainless Steel lid, a Steel box body, and 4 x Auto Switched GPO Outlets plus 5 x Data Provisions. Previously known as FFOB-255/80.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSF4P5DS80-SE**
Series	**FOBSSF4P5DS80-SE Flush Lid Floor Box**
Lid Material	**Stainless Steel, Hinged, Square Edge (245 x 245mm)**
Body Material	**Steel**
Outlet Configuration	**4 x 10 Amp Round Auto Switched Power Outlets + 5 x Data Outlet Clips**
Conduit Entry	**8 x Combination 25/32mm Knockouts (4 side, 4 base)**
Weight	**5.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 250×247×89 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
230×227×79 mm	**250×247×89** mm
RAISED FLOOR CUT-OUT	
232×229 mm	

KEY FEATURES

- Hinged, square edge Stainless Steel lid (245 x 245mm) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 230 x 227 x 79mm nominal depth
- 8 x combination 25/32mm conduit knockouts (4 on the outside of the box, 4 on the base)
- 4 x 10 Amp round auto switched power outlets
- 5 x single data outlet clips

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSSF4P5DS80-SE**
Series	**FOBSSF4P5DS80-SE Flush Lid Floor Box, Stainless Steel, Square Edge, 4 x Auto Switched GPO + 5 x Data**
Block-out in Concrete Slab	**250 x 247 x 89mm nominal**
Warranty	**Manufacturer's warranty**