1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES

Stainless Steel Recessed Deep Floor Box, Double GPO + 3 x Data

FOBSSR1STDO3DXL









The FOBSSR1STDO3DXL recessed lid floor box features a 14mm Stainless Steel hinged recessed lid, a Steel box body, and an outlet bracket for 1 x Double GPO Outlet plus 3 x Data Provisions. Previously known as FFOB-188.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSR1STDO3DXL**
Series	**FOBSSR1STDO3DXL Recessed Lid Floor Box**
Lid Material	**Stainless Steel Hinged Lid, 14mm Recessed (180 x 180mm)**
Body Material	**Steel**
Outlet Configuration	**1 x Double GPO Outlet + 3 x Data Provisions**
Conduit Entry	**10 x Combination 25/32mm Knockouts (8 side, 2 base)**
Weight	**2.7 kg (approx.)**

DIMENSIONS

Block-out in slab: 177×177×112 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
157×157×102 mm	**177×177×112** mm
RAISED FLOOR CUT-OUT	
159×159 mm	

KEY FEATURES

- Stainless Steel hinged lid (180 x 180mm, 14mm recessed rebate) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 157 x 157 x 102mm nominal depth
- 10 x combination 25/32mm conduit knockouts (8 on the sides, 2 on the base)
- Outlet bracket to suit 1 x Standard Series style Power/Data/AV outlet, plus 1 x 3-Gang Data outlet clip
- Floating floor brackets available upon request

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels

ORDERING INFORMATION

Part Number	**FOBSSR1STDO3DXL**
Series	**FOBSSR1STDO3DXL Recessed Lid Floor Box, Stainless Steel, 1 x Double GPO + 3 x Data**
Block-out in Concrete Slab	**177 x 177 x 112mm nominal**
Warranty	**Manufacturer's warranty**