1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES

Stainless Steel Recessed Deep Floor Box, 1 x Double GPO

FOBSSR1STDOXL









The FOBSSR1STDOXL recessed lid floor box features a 14mm Stainless Steel hinged recessed lid, a Steel box body, and an outlet bracket for 1 x Clipsal 2000 Series style Double GPO Outlet. Previously known as FFOB-185.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSR1STDOXL**
Series	**FOBSSR1STDOXL Recessed Lid Floor Box**
Lid Material	**Stainless Steel Hinged Lid, 14mm Recessed (180 x 180mm)**
Body Material	**Steel**
Outlet Configuration	**1 x Double GPO Outlet (Clipsal 2000 Series compatible bracket)**
Conduit Entry	**10 x Combination 25/32mm Knockouts (2 each side, 2 base)**
Weight	**2.6 kg (approx.)**

DIMENSIONS

Block-out in slab: 177×177×112 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
157×157×102 mm	**177×177×112** mm
RAISED FLOOR CUT-OUT	
159×159 mm	

KEY FEATURES

- Stainless Steel hinged lid (180 x 180mm, 14mm recessed rebate) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 157 x 157 x 102mm nominal depth
- 10 x combination 25/32mm conduit knockouts (2 on each side, 2 on the base)
- Outlet bracket to suit 1 x Clipsal 2000 Series style Power/Data/AV outlet; 1 x Double GPO Outlet supplied

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FOBSSR1STDOXL**
Series	**FOBSSR1STDOXL Recessed Lid Floor Box, Stainless Steel, 1 x Double GPO Outlet**
Block-out in Concrete Slab	**177 x 177 x 112mm nominal**
Warranty	**Manufacturer's warranty**