1300 302 249
sales@cableduct.com.au
www.cableduct.com.au

FLOOR BOXES — STAINLESS STEEL LID FLOOR BOXES


Stainless Steel Square Edge Recessed Floor Box, Quad GPO + 12 x Data

FOBSSR3STDO-SE









The FOBSSR3STDO-SE recessed lid floor box features a 14mm Stainless Steel hinged recessed lid, a Steel box body, and provisions for 1 x Quad GPO or Double GPO plus 12 x Data outlets, with brackets suited to Clipsal 2000 Series outlets. Previously known as FFOB-250.

TECHNICAL SPECIFICATIONS

Part Number	**FOBSSR3STDO-SE**
Series	**FOBSSR3STDO-SE Recessed Lid Floor Box**
Lid Material	**Stainless Steel Hinged Lid, 14mm Recessed (245 x 245mm)**
Body Material	**Steel**
Outlet Configuration	**1 x Quad GPO or Double GPO Provision + 12 x Data Provisions**
Conduit Entry	**13 x Combination 25/32mm Knockouts (10 side, 3 base)**
Weight	**5.0 kg (approx.)**

DIMENSIONS

Block-out in slab: 248×247×125 mm · dimensions nominal

BOX BODY	SLAB BLOCK-OUT
228×227×110 mm	**248×247×125** mm
RAISED FLOOR CUT-OUT	
230×229 mm	

KEY FEATURES

- Stainless Steel hinged lid (245 x 245mm, 14mm recessed rebate) screw-fixes to the steel box body
- 2 x cord exit flaps allow cords out with the main cover closed
- Temporary cover secures to the body during the concrete pour to prevent ingress of slurry
- Steel box body, 228 x 227 x 110mm nominal depth
- 13 x combination 25/32mm conduit knockouts (10 on the outside of the box, 3 on the base)
- Outlet bracket to suit 1 x Clipsal 2000 Gangbusters Series style Power/Data/AV outlet
- Outlet bracket to suit 2 x Clipsal 2000 Series style Power/Data/AV outlets

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels

ORDERING INFORMATION

Part Number	**FOBSSR3STDO-SE**
Series	**FOBSSR3STDO-SE Recessed Lid Floor Box, Stainless Steel, 1 x Quad/Double GPO + 12 x Data**
Block-out in Concrete Slab	**248 x 247 x 125mm nominal**
Warranty	**Manufacturer's warranty**