1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES — 145 SERIES

Floor Outlet Box 1 x Standard GPO + USB Charge A + C 19mm Brass Recessed Lid 145 Series

FB145BR19R1STDOUSB

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23







The FB145BR19R1STDOUSB floor outlet box has a brass 19 mm recessed lid and 1 x standard double GPO with USB-A and USB-C charging. It has a finished height of 128 mm, adjustable to 153 mm on the adjustable mounting bracket to suit the floor build-up. The 19 mm recess takes a tile or timber insert (by others).

TECHNICAL SPECIFICATIONS

Part Number	**FB145BR19R1STDOUSB**
Lid Type	**Recessed — 19 mm (tile or timber insert by others)**
Lid Finish	**Brass**
Carcass Type	**Standard (105 mm carcass)**
Finished Height	**128 mm**, adjustable to 153 mm via the adjustable mounting bracket
Outlet Configuration	**1 × standard double GPO with USB-A and USB-C charging, 1 × cable exit flap**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Brass**
Conduit Knockouts	**6 × Ø25 mm**
Weight	**3.0 kg (approx.)**

DIMENSIONS

Body: W 125 × L 125 mm (140 mm over fixing lugs) · Carcass depth 105 mm

FINISHED HEIGHT
128 mm
Adjustable to 153 mm via the adjustable mounting bracket

LID WIDTH	LID LENGTH
150 mm	**150 mm**

BODY WIDTH	CARCASS DEPTH
125 mm	**105 mm**

KEY FEATURES

- Brass 19 mm recessed lid — takes a tile or timber insert to match the floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 6 × Ø25 mm conduit knockouts for flexible cable routing
- Integrated USB-A + USB-C charging — no adaptor needed
- 1 power outlet pre-configured for immediate use
- Compatible with all 145 Series accessories and outlet inserts
- Finished height 128 mm, adjustable to 153 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FB145BR19R1STDOUSB**
Series	**145 Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**