1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES — 145 SERIES

# Floor Outlet Box 1 Standard GPO USB Charge (1 x USB-A and 1 x USB-C) Brass Flush 145 Series

**FB145BRF1STDOUSB**

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23






The FB145BRF1STDOUSB floor outlet box has a brass flush lid and 1 x standard double GPO with USB-A and USB-C charging. It has a finished height of 105 mm, adjustable to 130 mm on the adjustable mounting bracket to suit the floor build-up.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Part Number | **FB145BRF1STDOUSB** |
| Lid Type | **Flush Finish** |
| Lid Finish | **Brass** |
| Carcass Type | **Standard (105 mm carcass)** |
| Finished Height | **105 mm**, adjustable to 130 mm via the adjustable mounting bracket |
| Outlet Configuration | **1 × standard double GPO with USB-A and USB-C charging, 2 × cable exit flaps** |
| Body Material | **Powder Coated Zinc Anneal Steel** |
| Lid Material | **Brass** |
| Conduit Knockouts | **6 × Ø25 mm** |
| Weight | **3.0 kg (approx.)** |

## DIMENSIONS

Body: W 125 × L 125 mm (140 mm over fixing lugs) · Carcass depth 105 mm

FINISHED HEIGHT
**105 mm**
Adjustable to 130 mm via the adjustable mounting bracket

| LID WIDTH | LID LENGTH |
|---|---|
| **145 mm** | **145 mm** |

| BODY WIDTH | CARCASS DEPTH |
|---|---|
| **125 mm** | **105 mm** |

## KEY FEATURES

- Brass flush lid — sits level with the finished floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 6 × Ø25 mm conduit knockouts for flexible cable routing
- Integrated USB-A + USB-C charging — no adaptor needed
- 1 power outlet pre-configured for immediate use
- Compatible with all 145 Series accessories and outlet inserts
- Finished height 105 mm, adjustable to 130 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

## TYPICAL APPLICATIONS

| | |
|---|---|
| Commercial offices & open plan workspaces | Conference rooms & boardrooms |
| Retail & showroom fit-outs | Hospitality & hotels |
| Educational facilities | Residential installations |

## ORDERING INFORMATION

| | |
|---|---|
| Part Number | **FB145BRF1STDOUSB** |
| Series | **145 Series Floor Outlet Boxes** |
| Compliance | **AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved** |
| Installation | **By a licensed electrician per AS/NZS 3000 (Wiring Rules)** |
| Warranty | **Manufacturer's warranty** |