1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES — 145 SERIES

Shallow Floor Outlet Box 2 Power Stainless Steel Round Flush 145 Series

FB145CSSF2PS65

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23









The FB145CSSF2PS65 shallow floor outlet box has a stainless steel round flush lid and 2 × 10 A auto switched outlets. It has a finished height of just 67 mm, adjustable to 92 mm on the adjustable mounting bracket, so it suits shallow screeds, timber and raised floors.

TECHNICAL SPECIFICATIONS

Part Number	**FB145CSSF2PS65**
Lid Type	**Round Flush**
Lid Finish	**Stainless Steel**
Carcass Type	**Shallow (65 mm carcass)**
Finished Height	**67 mm**, adjustable to 92 mm via the adjustable mounting bracket
Outlet Configuration	**2 × 10 A auto switched outlets, 2 × cable exit flaps**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Stainless Steel (Round Profile)**
Conduit Knockouts	**6 × Ø25 mm**
Weight	**3.0 kg (approx.)**

DIMENSIONS

Body: W 125 × L 125 mm (140 mm over fixing lugs) · Carcass depth 65 mm

FINISHED HEIGHT
67 mm
Adjustable to 92 mm via the adjustable mounting bracket

LID DIAMETER	BODY LENGTH
200 mm	**125 mm**

BODY WIDTH	CARCASS DEPTH
125 mm	**65 mm**

KEY FEATURES

- Stainless Steel round flush lid (Ø200 mm) — sits level with the finished floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 6 × Ø25 mm conduit knockouts for flexible cable routing
- Compatible with all 145 Series accessories and outlet inserts
- Finished height 67 mm, adjustable to 92 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FB145CSSF2PS65**
Series	**145 Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**