



FLOOR OUTLET BOXES — 145 SERIES

Floor Outlet Box 1 Standard GPO (1 x USB-A and 1 x USB-C) Stainless Steel Flush lid 145 Series

FB145SSF1STD0USB



The FB145SSF1STD0USB floor outlet box features a stainless steel flush lid with 1 × Standard Double GPO + USB-A & USB-C Charge, delivering in-floor power via 1 standard double GPO. Small and compact, it delivers in-floor services with a clean finish.

TECHNICAL SPECIFICATIONS

Part Number	FB145SSF1STD0USB
Lid Type	Flush Finish
Lid Finish	Stainless Steel
Carcass Type	Standard Depth (105 mm)
Outlet Configuration	1 × Standard Double GPO + USB-A & USB-C Charge
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm (6)
Weight	3.0 kg (approx.)

DIMENSIONS

Body: W 125 × L 125 × D 110 mm including lid

LID WIDTH
145 mm

LID LENGTH
145 mm

BODY WIDTH
125 mm

BODY DEPTH
105 mm

KEY FEATURES

- Stainless Steel flush finish lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- Integrated USB-A + USB-C charging — no adaptor needed
- 1 power outlet pre-configured for immediate use
- Compatible with all 145 Series accessories and outlet inserts
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces

Conference rooms & boardrooms

Retail & showroom fit-outs

Hospitality & hotels

Educational facilities

Residential installations

ORDERING INFORMATION

Part Number	FB145SSF1STD0USB
Series	145 Series Floor Outlet Boxes
Warranty	Manufacturer's warranty