



FLOOR OUTLET BOXES — 245 SERIES

Floor Outlet Box 2 x 10amp Auto Switched Outlets 3 x Data - Stainless Steel Black Resseded (19mm) Lid 245 Series (Shallow)

FB245SS19BR2P3DS50

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23



The FB245SS19BR2P3D floor outlet box features a stainless steel flush lid, providing 2 power and 3 data provisions for comprehensive connectivity. Designed for high-demand commercial environments requiring maximum outlet density.

TECHNICAL SPECIFICATIONS

Part Number	FB245SS19BR2P3DS50
Lid Type	Flush Finish
Lid Finish	Stainless Steel
Carcass Type	Standard Depth (105 mm)
Outlet Configuration	2 × Power + 3 × Data provisions
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm (4 sides)
Weight	6.0 kg (approx.)

DIMENSIONS

Body: W 220 × L 220 × D 105 mm			
LID WIDTH	245 mm	LID LENGTH	245 mm
BODY WIDTH	220 mm	BODY DEPTH	52 mm

KEY FEATURES

- Stainless Steel flush finish lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- 2 power + 3 data provisions — single-box AV and power solution
- Compatible with all 245 Series accessories and outlet inserts
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Large boardrooms & meeting rooms	Conference rooms & boardrooms
Exhibition halls & event spaces	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	FB245SS19BR2P3D
Series	245 Series Floor Outlet Boxes
Compliance	AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved
Installation	By a licensed electrician per AS/NZS 3000 (Wiring Rules)
Warranty	Manufacturer's warranty