1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES — 245 SERIES

Floor Outlet Box 2 x 10amp Auto Switched Outlets 3 x Data Provisions - Stainless Steel Recessed (19mm) 245 Series (Shallow)

FB245SS19R2P3DS50

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23






The FB245SS19R2P3DS50 shallow 245 Series floor outlet box has a stainless steel 19 mm recessed lid and 2 x 10 A auto switched outlets, provision for 3 x data. It has a finished height of 74 mm, adjustable to 99 mm on the adjustable mounting bracket to suit the floor build-up. The 19 mm recess takes a tile or timber insert (by others).

TECHNICAL SPECIFICATIONS

Part Number	**FB245SS19R2P3DS50**
Lid Type	**Recessed — 19 mm (tile or timber insert by others)**
Lid Finish	**Stainless Steel**
Carcass Type	**Shallow (50 mm carcass)**
Finished Height	**74 mm, adjustable to 99 mm via the adjustable mounting bracket**
Outlet Configuration	**2 × 10 A auto switched outlets, provision for 3 × data, 1 × cable exit flap**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Stainless Steel**
Conduit Knockouts	**12 × Ø25 mm**
Weight	**2.2 kg (approx.)**

DIMENSIONS

Body: W 225 × L 125 mm (140 mm over fixing lugs) · Carcass depth 50 mm

FINISHED HEIGHT
74 mm
Adjustable to 99 mm via the adjustable mounting bracket

LID WIDTH	LID LENGTH
250 mm	**150 mm**

BODY WIDTH	CARCASS DEPTH
225 mm	**50 mm**

KEY FEATURES

- Stainless Steel 19 mm recessed lid — takes a tile or timber insert to match the floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 12 × Ø25 mm conduit knockouts for flexible cable routing
- 2 power + 3 data provisions — single-box AV and power solution
- Shallow 50 mm carcass — ideal for limited-depth floor installations
- Compatible with all 245 Series accessories and outlet inserts
- Finished height 74 mm, adjustable to 99 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Large boardrooms & meeting rooms	Conference rooms & boardrooms
Exhibition halls & event spaces	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FB245SS19R2P3DS50**
Series	**245 Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**