



FLOOR OUTLET BOXES — 245 SERIES

Floor Outlet Box 2 Standard Outlet Provisions Stainless Steel 19mm Recessed Lid 245 Series

FB245SS19R2STD0



The FB245SS19R2STD0 floor outlet box features a stainless steel recessed 19mm lid, delivering in-floor power via 2 standard double GPOs. Designed for high-demand commercial environments requiring maximum outlet density.

TECHNICAL SPECIFICATIONS

Part Number	FB245SS19R2STD0
Lid Type	Recessed — 19 mm
Lid Finish	Stainless Steel
Carcass Type	Standard Depth (107 mm)
Outlet Configuration	2 × Standard Double GPO
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm (12)
Weight	4.0 kg (approx.)

DIMENSIONS

Body: W 150 × L 225 × D 128 mm including lid

LID WIDTH

150 mm

LID LENGTH

250 mm

BODY WIDTH

125 x 225 mm

BODY DEPTH

107 mm

KEY FEATURES

- Stainless Steel recessed — 19 mm lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- 2 power outlets pre-configured for immediate use
- Compatible with all 245 Series accessories and outlet inserts
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Large boardrooms & meeting rooms

Conference rooms & boardrooms

Exhibition halls & event spaces

Hospitality & hotels

Educational facilities

Residential installations

ORDERING INFORMATION

Part Number	FB245SS19R2STD0
Series	245 Series Floor Outlet Boxes
Warranty	Manufacturer's warranty