1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES & FLOOR BOXES

4 Power 10 Data Brass Flush Lid Floor Outlet Box

FBBRF4P10D

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23









The FBBRF4P10D standard-depth floor outlet box has a brass flush lid and 4 x 10 A auto switched outlets, provision for 10 x data. It has a finished height of 94 mm, adjustable to 119 mm on the adjustable mounting bracket to suit the floor build-up.

TECHNICAL SPECIFICATIONS

Part Number	**FBBRF4P10D**
Lid Type	**Flush Finish**
Lid Finish	**Brass**
Carcass Type	**Standard (90 mm carcass)**
Finished Height	**94 mm, adjustable to 119 mm via the adjustable mounting bracket**
Outlet Configuration	**4 × 10 A auto switched outlets, provision for 10 × data, 1 × cable exit flap**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Brass**
Conduit Knockouts	**10 × Ø25 mm and 4 × Ø20 mm**
Weight	**3.0 kg (approx.)**

DIMENSIONS

Body: W 227 × L 194 mm (250 mm over fixing lugs) · Carcass depth 90 mm

FINISHED HEIGHT
94 mm
Adjustable to 119 mm via the adjustable mounting bracket

LID WIDTH	LID LENGTH
250 mm	**220 mm**

BODY WIDTH	CARCASS DEPTH
227 mm	**90 mm**

KEY FEATURES

- Brass flush lid — sits level with the finished floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 10 × Ø25 mm and 4 × Ø20 mm conduit knockouts for flexible cable routing
- 4 power + 10 data provisions — single-box AV and power solution
- Finished height 94 mm, adjustable to 119 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

High-density AV & data installations	Conference rooms & boardrooms
Trading floors & dealing rooms	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FBBRF4P10D**
Series	**Standard Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**