



FLOOR OUTLET BOXES & FLOOR BOXES

## 2 Power 4 Data Shallow Stainless Steel 14mm Recessed lid Floor Outlet Box

**FBSS14R2P4DS50**



The FBSS14R2P4DS50 floor outlet box features a stainless steel recessed 14mm lid, providing 2 power and 4 data provisions for comprehensive connectivity. The shallow 54 mm depth suits installations where floor depth is limited. Built for reliable in-floor service delivery in commercial and residential projects.

### TECHNICAL SPECIFICATIONS

Part Number	FBSS14R2P4DS50
Lid Type	Recessed — 14 mm
Lid Finish	Stainless Steel
Carcass Type	Shallow Depth (50 mm)
Outlet Configuration	2 × Power + 4 × Data provisions
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm ( 10 )
Weight	4.0 kg (approx.)

### DIMENSIONS

Body: W 194 x L 227 x D 70 mm including lid

LID WIDTH  
**194** mm

LID LENGTH  
**227** mm

BODY WIDTH  
**194 x 227** mm

BODY DEPTH  
**50** mm

### KEY FEATURES

- Stainless Steel recessed — 14 mm lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- 2 power + 4 data provisions — single-box AV and power solution
- Shallow 54 mm body depth — ideal for limited-depth floor installations
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

### TYPICAL APPLICATIONS

Commercial offices & open plan workspaces

Conference rooms & boardrooms

Retail & showroom fit-outs

Hospitality & hotels

Educational facilities

Residential installations

### ORDERING INFORMATION

Part Number	FBSS14R2P4DS50
Series	Standard Series Floor Outlet Boxes
Warranty	Manufacturer's warranty