



FLOOR OUTLET BOXES & FLOOR BOXES

2 Power 6 Data Shallow Stainless Steel 14mm Recessed lid Floor Outlet Box

FBSS14R2P6DS50



The FBSS14R2P6DS50 floor outlet box features a stainless steel recessed 14mm lid, providing 2 power and 6 data provisions for comprehensive connectivity. The shallow 54 mm depth suits installations where floor depth is limited. Built for reliable in-floor service delivery in commercial and residential projects.

TECHNICAL SPECIFICATIONS

Part Number	FBSS14R2P6DS50
Lid Type	Recessed — 14 mm
Lid Finish	Stainless Steel
Carcass Type	Shallow Depth (50 mm)
Outlet Configuration	2 × Power + 6 × Data provisions
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm (10)
Weight	4.0 kg (approx.)

DIMENSIONS

Body: W194 x L 227 x D 70 mm including lid

LID WIDTH

194 mm

LID LENGTH

230 mm

BODY WIDTH

194 x 227 mm

BODY DEPTH

50 mm

KEY FEATURES

- Stainless Steel recessed — 14 mm lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- 2 power + 6 data provisions — single-box AV and power solution
- Shallow 54 mm body depth — ideal for limited-depth floor installations
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces

Conference rooms & boardrooms

Retail & showroom fit-outs

Hospitality & hotels

Educational facilities

Residential installations

ORDERING INFORMATION

Part Number	FBSS14R2P6DS50
Series	Standard Series Floor Outlet Boxes
Warranty	Manufacturer's warranty