1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES & FLOOR BOXES

Shallow Floor Box with Stainless Steel 14mm Recessed Square Edge lid complete with 4 x power 4 x Data 54mm Shallow Carcass

FBSS14R4P6DS50

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23






The FBSS14R4P6DS50 shallow floor outlet box has a stainless steel 14 mm recessed lid and 4 x 10 A auto switched outlets, provision for 6 x data. It has a finished height of 70 mm, adjustable to 95 mm on the adjustable mounting bracket to suit the floor build-up. The 14 mm recess takes a tile or timber insert (by others).

TECHNICAL SPECIFICATIONS

Part Number	**FBSS14R4P6DS50**
Lid Type	**Recessed — 14 mm (tile or timber insert by others)**
Lid Finish	**Stainless Steel**
Carcass Type	**Shallow (50 mm carcass)**
Finished Height	**70 mm, adjustable to 95 mm via the adjustable mounting bracket**
Outlet Configuration	**4 × 10 A auto switched outlets, provision for 6 × data, 1 × cable exit flap**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Stainless Steel**
Conduit Knockouts	**12 × Ø25 mm and 4 × Ø20 mm**
Weight	**2.2 kg (approx.)**

DIMENSIONS

Body: W 227 × L 194 mm (214 mm over fixing lugs) · Carcass depth 50 mm

FINISHED HEIGHT
70 mm
Adjustable to 95 mm via the adjustable mounting bracket

LID WIDTH	LID LENGTH
230 mm	**195 mm**

BODY WIDTH	CARCASS DEPTH
227 mm	**50 mm**

KEY FEATURES

- Stainless Steel 14 mm recessed lid — takes a tile or timber insert to match the floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 12 × Ø25 mm and 4 × Ø20 mm conduit knockouts for flexible cable routing
- 4 power + 6 data provisions — single-box AV and power solution
- Shallow 50 mm carcass — ideal for limited-depth floor installations
- Finished height 70 mm, adjustable to 95 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FBSS14R4P6DS50**
Series	**Standard Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**