1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES & FLOOR BOXES

# 2 Power 6 Data Shallow Stainless Steel 19mm Recessed lid Floor Outlet Box

**FBSS19R2P6DS50**

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23









The FBSS19R2P6DS50 shallow floor outlet box has a stainless steel 19 mm recessed lid and 2 x 10 A auto switched outlets, provision for 6 x data. It has a finished height of 75 mm, adjustable to 100 mm on the adjustable mounting bracket to suit the floor build-up. The 19 mm recess takes a tile or timber insert (by others).

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Part Number | **FBSS19R2P6DS50** |
| Lid Type | **Recessed — 19 mm (tile or timber insert by others)** |
| Lid Finish | **Stainless Steel** |
| Carcass Type | **Shallow (50 mm carcass)** |
| Finished Height | **75 mm, adjustable to 100 mm via the adjustable mounting bracket** |
| Outlet Configuration | **2 × 10 A auto switched outlets, provision for 6 × data, 1 × cable exit flap** |
| Body Material | **Powder Coated Zinc Anneal Steel** |
| Lid Material | **Stainless Steel** |
| Conduit Knockouts | **12 × Ø25 mm and 4 × Ø20 mm** |
| Weight | **2.2 kg (approx.)** |

## DIMENSIONS

Body: W 227 × L 194 mm (214 mm over fixing lugs) · Carcass depth 50 mm

FINISHED HEIGHT
**75 mm**
Adjustable to 100 mm via the adjustable mounting bracket

| LID WIDTH | LID LENGTH |
|---|---|
| **230 mm** | **195 mm** |

| BODY WIDTH | CARCASS DEPTH |
|---|---|
| **227 mm** | **50 mm** |

## KEY FEATURES

- Stainless Steel 19 mm recessed lid — takes a tile or timber insert to match the floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 12 × Ø25 mm and 4 × Ø20 mm conduit knockouts for flexible cable routing
- 2 power + 6 data provisions — single-box AV and power solution
- Shallow 50 mm carcass — ideal for limited-depth floor installations
- Finished height 75 mm, adjustable to 100 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

## TYPICAL APPLICATIONS

| | |
|---|---|
| Commercial offices & open plan workspaces | Conference rooms & boardrooms |
| Retail & showroom fit-outs | Hospitality & hotels |
| Educational facilities | Residential installations |

## ORDERING INFORMATION

| | |
|---|---|
| Part Number | **FBSS19R2P6DS50** |
| Series | **Standard Series Floor Outlet Boxes** |
| Compliance | **AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved** |
| Installation | **By a licensed electrician per AS/NZS 3000 (Wiring Rules)** |
| Warranty | **Manufacturer's warranty** |