
1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES & FLOOR BOXES

Shallow Floor Box Stainless Steel Flush Square Edge Lid complete with 2 x power 4 x Data 54mm Shallow Carcass

FBSSF2P4DS50-SE

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23






The FBSSF2P4DS50-SE shallow floor outlet box has a stainless steel square edge flush lid and 2 x 10 A auto switched outlets, provision for 4 x data. It has a finished height of 58 mm, adjustable to 83 mm on the adjustable mounting bracket to suit the floor build-up.

TECHNICAL SPECIFICATIONS

Part Number	**FBSSF2P4DS50-SE**
Lid Type	**Square Edge Flush**
Lid Finish	**Stainless Steel**
Carcass Type	**Shallow (50 mm carcass)**
Finished Height	**58 mm**, adjustable to 83 mm via the adjustable mounting bracket
Outlet Configuration	**2 × 10 A auto switched outlets, provision for 4 × data, 1 × cable exit flap**
Body Material	**Powder Coated Zinc Anneal Steel**
Lid Material	**Stainless Steel**
Conduit Knockouts	**12 × Ø25 mm and 4 × Ø20 mm**
Weight	**2.2 kg (approx.)**

DIMENSIONS

Body: W 227 × L 194 mm (214 mm over fixing lugs) · Carcass depth 50 mm

FINISHED HEIGHT
58 mm
Adjustable to 83 mm via the adjustable mounting bracket

LID WIDTH	LID LENGTH
250 mm	**220 mm**

BODY WIDTH	CARCASS DEPTH
227 mm	**50 mm**

KEY FEATURES

- Stainless Steel square edge flush lid — sits level with the finished floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 12 × Ø25 mm and 4 × Ø20 mm conduit knockouts for flexible cable routing
- 2 power + 4 data provisions — single-box AV and power solution
- Shallow 50 mm carcass — ideal for limited-depth floor installations
- Square-edge lid profile — contemporary look for modern commercial fit-outs
- Finished height 58 mm, adjustable to 83 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	**FBSSF2P4DS50-SE**
Series	**Standard Series Floor Outlet Boxes**
Compliance	**AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved**
Installation	**By a licensed electrician per AS/NZS 3000 (Wiring Rules)**
Warranty	**Manufacturer's warranty**