1300 883 452
sales@cableaway.com.au
Unit 8, 15 McPherson Road, Smeaton Grange NSW 2567
www.cableaway.com.au

FLOOR OUTLET BOXES & FLOOR BOXES

# 2 Power 8 Data Stainless Steel Square Edge Flush Floor Outlet Box

**FBSSF2P8D-SE**

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23









The FBSSF2P8D-SE standard-depth floor outlet box has a stainless steel square edge flush lid and 2 x 10 A auto switched outlets, provision for 8 x data. It has a finished height of 98 mm, adjustable to 123 mm on the adjustable mounting bracket to suit the floor build-up.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Part Number | **FBSSF2P8D-SE** |
| Lid Type | **Square Edge Flush** |
| Lid Finish | **Stainless Steel** |
| Carcass Type | **Standard (90 mm carcass)** |
| Finished Height | **98 mm, adjustable to 123 mm via the adjustable mounting bracket** |
| Outlet Configuration | **2 × 10 A auto switched outlets, provision for 8 × data, 1 × cable exit flap** |
| Body Material | **Powder Coated Zinc Anneal Steel** |
| Lid Material | **Stainless Steel** |
| Conduit Knockouts | **10 × Ø25 mm and 4 × Ø20 mm** |
| Weight | **3.0 kg (approx.)** |

## DIMENSIONS

Body: W 227 × L 194 mm (250 mm over fixing lugs) · Carcass depth 90 mm

FINISHED HEIGHT
**98 mm**
Adjustable to 123 mm via the adjustable mounting bracket

| LID WIDTH | LID LENGTH |
|---|---|
| **250 mm** | **220 mm** |

| BODY WIDTH | CARCASS DEPTH |
|---|---|
| **227 mm** | **90 mm** |

## KEY FEATURES

- Stainless Steel square edge flush lid — sits level with the finished floor
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 10 × Ø25 mm and 4 × Ø20 mm conduit knockouts for flexible cable routing
- 2 power + 8 data provisions — single-box AV and power solution
- Square-edge lid profile — contemporary look for modern commercial fit-outs
- Finished height 98 mm, adjustable to 123 mm on the adjustable mounting bracket to suit the floor build-up
- Suitable for concrete, timber, and raised floor installations

## TYPICAL APPLICATIONS

| | |
|---|---|
| High-density AV & data installations | Conference rooms & boardrooms |
| Trading floors & dealing rooms | Hospitality & hotels |
| Educational facilities | Residential installations |

## ORDERING INFORMATION

| | |
|---|---|
| Part Number | **FBSSF2P8D-SE** |
| Series | **Standard Series Floor Outlet Boxes** |
| Compliance | **AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved** |
| Installation | **By a licensed electrician per AS/NZS 3000 (Wiring Rules)** |
| Warranty | **Manufacturer's warranty** |