



FLOOR OUTLET BOXES & FLOOR BOXES

2 Power 4 Data Stainless Steel Recessed Lid Floor Outlet Box

FBSSR2P4D

RCM SAA AS/NZS 3100 · 3112 · 3133 · IEC 60670.23



The FBSSR2P4D floor outlet box features a stainless steel recessed lid, providing 2 power and 4 data provisions for comprehensive connectivity. Built for reliable in-floor service delivery in commercial and residential projects.

TECHNICAL SPECIFICATIONS

Part Number	FBSSR2P4D
Lid Type	Recessed
Lid Finish	Stainless Steel
Carcass Type	Standard Depth (105 mm)
Outlet Configuration	2 × Power + 4 × Data provisions
Body Material	Powder Coated Zinc Anneal Steel
Lid Material	Stainless Steel
Conduit Knockouts	25 mm (4 sides)
Weight	3.0 kg (approx.)

DIMENSIONS

Body: See dimensions × D 105 mm			
LID WIDTH		LID LENGTH	
see web mm		see web mm	
BODY WIDTH		BODY DEPTH	
see web mm		105 mm	

KEY FEATURES

- Stainless Steel recessed lid — precise alignment with any floor surface
- Powder coated zinc anneal steel body for durability and corrosion resistance
- 25 mm (4 sides) conduit knockouts for flexible cable routing
- 2 power + 4 data provisions — single-box AV and power solution
- Height-adjustable lid mechanism for perfect flush with floor finish
- Suitable for concrete, timber, and raised floor installations

TYPICAL APPLICATIONS

Commercial offices & open plan workspaces	Conference rooms & boardrooms
Retail & showroom fit-outs	Hospitality & hotels
Educational facilities	Residential installations

ORDERING INFORMATION

Part Number	FBSSR2P4D
Series	Standard Series Floor Outlet Boxes
Compliance	AS/NZS 3100, 3112, 3133, IEC 60670.23 — RCM & SAA approved
Installation	By a licensed electrician per AS/NZS 3000 (Wiring Rules)
Warranty	Manufacturer's warranty