1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — BRASS SERIES

CLOSED **IP66 / IK07** | OPEN **IP20 / IK06** | CERTIFIED **RCM & SAA**

# IP66 Rated Floor Outlet Box — Brass Lid, 1 x 10A Auto Switched Power Outlet

**FOBBR1P-IP66**



The FOBBR1P-IP66 is a heavy-duty IP66 rated in-floor outlet box designed for outdoor and wet-area power distribution. Featuring a flush Brass Mechanism Holding Unit, it houses 1 x 10 Amp Auto-Switched Square GPO for reliable power access in exposed environments. The solid Fireproof Thermoplastic body withstands the demands of both construction and long-term service. Supplied with an MDF Temporary Lid to prevent slurry ingress during concrete pour. Allen Key Locking System available on request. Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements.

## DIMENSIONS

| 130 x 130 | 135 x 135 x 69 | 155 x 155 x 79 |
|---|---|---|
| mm | mm | mm |
| Lid Size | Box Body | Recess / Block-out |

## KEY FEATURES

- IP66 rated (closed) — fully protected against powerful water jets
- IK07 impact resistance rating when closed
- Flush brass lid for a premium, durable finish in outdoor environments
- 1 x 10A Auto-Switched GPO — power available when lid is opened
- Fireproof Thermoplastic body — 135 x 135 x 69mm nominal depth
- MDF Temporary Lid included for protection during concrete pour
- Allen Key Locking System available on request for added security
- Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements

## TYPICAL APPLICATIONS

| | |
|---|---|
| Outdoor commercial areas & plazas | Alfresco dining & hospitality |
| Retail precincts & shopping centres | Industrial & warehouse floors |
| Swimming pool surrounds & aquatic centres | Sports fields & stadiums |
| Marine & waterside environments | Wet area & washdown zones |

1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — BRASS SERIES

# IP66 Rated Floor Outlet Box — Brass Lid, 1 x 10A Auto Switched Power Outlet

PART NO. **FOBBR1P-IP66** · TECHNICAL & ORDERING DETAILS

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Lid Size | **130 x 130mm** |
| Box Body | **135 x 135 x 69mm nominal depth** |
| Recess / Block-out | **155 x 155 x 79mm nominal** |
| Box Material | **Fireproof Thermoplastic** |
| IP Rating (Closed) | **IP66** |
| IP Rating (Open) | **IP20** |
| IK Rating (Closed) | **IK07** |
| IK Rating (Open) | **IK06** |
| Temperature | **-15°C to +60°C (installation); +90°C max on-site** |
| Compliance | **AS3000 / SAA Wiring Rules / A.C.A Requirements** |
| Includes | **MDF Temporary Lid** |
| Lid Finish | **Brass Flush Lid** |
| Locking | **Brass Mechanism Holding Unit** |
| Optional Locking | **Allen Key Locking System (on request)** |
| Outlet | **1 x 10A Auto-Switched Square GPO** |

## COMPLIANCE & INSTALLATION NOTES

Complies with AS/NZS 3100, 3112, 3133 & IEC 60670.23. RCM & SAA approved. Block-out: 155 x 155 x 79mm nominal. Must be installed by a licensed electrician in accordance with AS/NZS 3000 (Wiring Rules). For Allen Key security locking, request FOBBR1P-IP66 with Allen Key Locking System option.

## ORDERING INFORMATION

| | |
|---|---|
| Part Number | **FOBBR1P-IP66** |
| Description | **IP66 Floor Box — Brass Lid, 1 x 10A Auto Switched GPO** |
| Lid Finish | **Brass Flush** |
| Optional | **Allen Key Locking System — available on request** |
| Warranty | **Manufacturer's warranty** |