1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — BRASS SERIES

CLOSED **IP66 / IK07** | OPEN **IP20 / IK06** | CERTIFIED **RCM & SAA**

IP66 Rated Floor Outlet Box — Brass Flush Lid, 2 x Data Outlets

FOBBR2D-IP66



The FOBBR2D-IP66 is a heavy-duty IP66 rated in-floor outlet box providing protected data connectivity in outdoor and wet-area environments. Featuring a flush Brass Mechanism Holding Unit, it accommodates 2 x Data outlets — ideal for network, AV, or communications services in exposed locations. The Fireproof Thermoplastic body delivers long-term durability in demanding conditions. Supplied with an MDF Temporary Lid to prevent slurry ingress during concrete pour. Allen Key Locking System available on request. Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements.

DIMENSIONS

130 x 130 mm	135 x 135 x 69 mm	155 x 155 x 79 mm
Lid Size	Box Body	Recess / Block-out

KEY FEATURES

- IP66 rated (closed) — fully protected against powerful water jets
- IK07 impact resistance rating when closed
- Flush brass lid for a premium finish in outdoor environments
- 2 x Data outlet provisions for network, AV or communications services
- Fireproof Thermoplastic body — 135 x 135 x 69mm nominal depth
- MDF Temporary Lid included for protection during concrete pour
- Allen Key Locking System available on request for added security
- Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements

TYPICAL APPLICATIONS

Outdoor commercial areas & plazas	Alfresco dining & hospitality
Retail precincts & shopping centres	Industrial & warehouse floors
Swimming pool surrounds & aquatic centres	Sports fields & stadiums
Marine & waterside environments	Wet area & washdown zones

1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — BRASS SERIES

IP66 Rated Floor Outlet Box — Brass Flush Lid, 2 x Data Outlets

PART NO. **FOBBR2D-IP66** · TECHNICAL & ORDERING DETAILS

TECHNICAL SPECIFICATIONS

Lid Size	**130 x 130mm**
Box Body	**135 x 135 x 69mm nominal depth**
Recess / Block-out	**155 x 155 x 79mm nominal**
Box Material	**Fireproof Thermoplastic**
IP Rating (Closed)	**IP66**
IP Rating (Open)	**IP20**
IK Rating (Closed)	**IK07**
IK Rating (Open)	**IK06**
Temperature	**-15°C to +60°C (installation); +90°C max on-site**
Compliance	**AS3000 / SAA Wiring Rules / A.C.A Requirements**
Includes	**MDF Temporary Lid**
Lid Finish	**Brass Flush Lid**
Locking	**Brass Mechanism Holding Unit**
Optional Locking	**Allen Key Locking System (on request)**
Data Outlets	**2 x Data Outlet Provisions**

COMPLIANCE & INSTALLATION NOTES

Complies with AS/NZS 3100, 3112, 3133 & IEC 60670.23. RCM & SAA approved. Block-out: 155 x 155 x 79mm nominal. Data modules / keystones not included. Must be installed by a licensed electrician or data cabling contractor in accordance with AS/NZS 3000 (Wiring Rules). For Allen Key security locking, request with Allen Key Locking System option.

ORDERING INFORMATION

Part Number	**FOBBR2D-IP66**
Description	**IP66 Floor Box — Brass Flush Lid, 2 x Data Outlets**
Lid Finish	**Brass Flush**
Optional	**Allen Key Locking System — available on request**
Warranty	**Manufacturer's warranty**