1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — STAINLESS STEEL SERIES

CLOSED **IP66 / IK07** | OPEN **IP20 / IK06** | CERTIFIED **RCM & SAA**

# IP66 Rated Floor Outlet Box — Stainless Steel Lid, 1 x 10A Auto Switched Power Outlet (Allen Key Lockable)

**FOBSS1P-IP66**



The FOBSS1P-IP66 is a premium IP66 rated in-floor outlet box designed for outdoor and high-security power distribution. Featuring a flush Stainless Steel Mechanism Holding Unit with Allen Key Locking System, it houses 1 x 10 Amp Auto-Switched Square GPO. The brushed stainless steel lid provides outstanding corrosion resistance for harsh outdoor environments. The Fireproof Thermoplastic body ensures long-term durability. Supplied with an MDF Temporary Lid to prevent concrete ingress during pour. Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements.

## DIMENSIONS

| 130 x 130 mm | 135 x 135 x 69 mm | 155 x 155 x 79 mm |
|---|---|---|
| Lid Size | Box Body | Recess / Block-out |

## KEY FEATURES

- IP66 rated (closed) — fully protected against powerful water jets
- IK07 impact resistance rating when closed
- Brushed stainless steel flush lid — premium corrosion-resistant finish
- Allen Key Locking System standard — enhanced tamper and vandal resistance
- 1 x 10A Auto-Switched GPO — power available when lid is opened
- Fireproof Thermoplastic body — 135 x 135 x 69mm nominal depth
- MDF Temporary Lid included for protection during concrete pour
- Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements

## TYPICAL APPLICATIONS

| | |
|---|---|
| Outdoor commercial areas & plazas | Alfresco dining & hospitality |
| Retail precincts & shopping centres | Industrial & warehouse floors |
| Swimming pool surrounds & aquatic centres | Sports fields & stadiums |
| Marine & waterside environments | Wet area & washdown zones |

1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — STAINLESS STEEL SERIES

# IP66 Rated Floor Outlet Box — Stainless Steel Lid, 1 x 10A Auto Switched Power Outlet (Allen Key Lockable)

PART NO. **FOBSS1P-IP66** · TECHNICAL & ORDERING DETAILS

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Lid Size | **130 x 130mm** |
| Box Body | **135 x 135 x 69mm nominal depth** |
| Recess / Block-out | **155 x 155 x 79mm nominal** |
| Box Material | **Fireproof Thermoplastic** |
| IP Rating (Closed) | **IP66** |
| IP Rating (Open) | **IP20** |
| IK Rating (Closed) | **IK07** |
| IK Rating (Open) | **IK06** |
| Temperature | **-15°C to +60°C (installation); +90°C max on-site** |
| Compliance | **AS3000 / SAA Wiring Rules / A.C.A Requirements** |
| Includes | **MDF Temporary Lid** |
| Lid Finish | **Stainless Steel Flush Lid** |
| Locking | **Allen Key Locking System (standard)** |
| Outlet | **1 x 10A Auto-Switched Square GPO** |

## COMPLIANCE & INSTALLATION NOTES

Complies with AS/NZS 3100, 3112, 3133 & IEC 60670.23. RCM & SAA approved. Block-out: 155 x 155 x 79mm nominal. Allen Key Locking System included as standard with this model. Must be installed by a licensed electrician in accordance with AS/NZS 3000 (Wiring Rules).

## ORDERING INFORMATION

| | |
|---|---|
| Part Number | **FOBSS1P-IP66** |
| Description | **IP66 Floor Box — SS Lid, 1 x 10A Auto Switched GPO, Allen Key Lock** |
| Lid Finish | **Stainless Steel Flush** |
| Locking | **Allen Key Locking System — standard** |
| Warranty | **Manufacturer's warranty** |