1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — STAINLESS STEEL SERIES

CLOSED **IP66 / IK07** | OPEN **IP20 / IK06** | CERTIFIED **RCM & SAA**

IP66 Rated Floor Outlet Box — Stainless Steel Flush Lid, 2 x Data Outlets (Allen Key Lock)

FOBSS2D-IP66



The FOBSS2D-IP66 is a premium IP66 rated in-floor outlet box providing secure, protected data connectivity in outdoor and high-security environments. Featuring a flush Stainless Steel Mechanism Holding Unit with Allen Key Locking System, it accommodates 2 x Data outlets for network, AV, or communications services. The brushed stainless steel lid delivers outstanding corrosion and impact resistance for demanding outdoor applications. The Fireproof Thermoplastic body ensures long-term reliability. Supplied with an MDF Temporary Lid for protection during concrete pour. Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements.

DIMENSIONS

130 x 130	135 x 135 x 69	155 x 155 x 79
mm	mm	mm
Lid Size	Box Body	Recess / Block-out

KEY FEATURES

- IP66 rated (closed) — fully protected against powerful water jets
- IK07 impact resistance rating when closed
- Brushed stainless steel flush lid — premium corrosion-resistant finish
- Allen Key Locking System standard — enhanced tamper and vandal resistance
- 2 x Data outlet provisions for network, AV or communications services
- Fireproof Thermoplastic body — 135 x 135 x 69mm nominal depth
- MDF Temporary Lid included for protection during concrete pour
- Compliant with AS3000, SAA Wiring Rules, and A.C.A Requirements

TYPICAL APPLICATIONS

Outdoor commercial areas & plazas	Alfresco dining & hospitality
Retail precincts & shopping centres	Industrial & warehouse floors
Swimming pool surrounds & aquatic centres	Sports fields & stadiums
Marine & waterside environments	Wet area & washdown zones

1300 883 452
sales@cableaway.com.au
www.cableaway.com.au

IP-RATED FLOOR OUTLET BOXES — STAINLESS STEEL SERIES

IP66 Rated Floor Outlet Box — Stainless Steel Flush Lid, 2 x Data Outlets (Allen Key Lock)

PART NO. **FOBSS2D-IP66** · TECHNICAL & ORDERING DETAILS

TECHNICAL SPECIFICATIONS

Lid Size	**130 x 130mm**
Box Body	**135 x 135 x 69mm nominal depth**
Recess / Block-out	**155 x 155 x 79mm nominal**
Box Material	**Fireproof Thermoplastic**
IP Rating (Closed)	**IP66**
IP Rating (Open)	**IP20**
IK Rating (Closed)	**IK07**
IK Rating (Open)	**IK06**
Temperature	**-15°C to +60°C (installation); +90°C max on-site**
Compliance	**AS3000 / SAA Wiring Rules / A.C.A Requirements**
Includes	**MDF Temporary Lid**
Lid Finish	**Stainless Steel Flush Lid**
Locking	**Allen Key Locking System (standard)**
Data Outlets	**2 x Data Outlet Provisions**

COMPLIANCE & INSTALLATION NOTES

Complies with AS/NZS 3100, 3112, 3133 & IEC 60670.23. RCM & SAA approved. Block-out: 155 x 155 x 79mm nominal. Data modules / keystones not included. Allen Key Locking System included as standard with this model. Must be installed by a licensed electrician or data cabling contractor in accordance with AS/NZS 3000 (Wiring Rules).

ORDERING INFORMATION

Part Number	**FOBSS2D-IP66**
Description	**IP66 Floor Box — SS Flush Lid, 2 x Data Outlets, Allen Key Lock**
Lid Finish	**Stainless Steel Flush**
Locking	**Allen Key Locking System — standard**
Warranty	**Manufacturer's warranty**