




SP100100 SERIES SERVICE COLUMN — 100 X 100MM (NATURAL ANODISED)

SP100100 Service Column — 100 x 100mm, 1 Division (Natural Anodised)

SP100100-1DIV-ANODISED



Cableaway's SP100100 service column is manufactured from strong and lightweight extruded aluminium, providing an easy, attractive and economical way to distribute power and telecommunications cabling from an open ceiling space down to desk or workstation height. At 100 x 100mm with 1 division, it suits a single cable run or compact single-outlet drop. Each pole ships as a complete kit — extruded column, Divider, Escutcheon Plate, Internal Foot Plate — ready to install without sourcing separate mounting hardware. Available in 3m, 4m and 6m standard lengths in Natural Anodised finish. Typical applications include office workstations, classrooms, retail outlets and factory floors.

TECHNICAL SPECIFICATIONS

Series Reference	SP100100-1DIV-ANODISED
Column Size	100 x 100mm
Divisions	1 (single cable channel)
Standard Lengths	3.0m, 4.0m, 6.0m
Body Material	Extruded Aluminium
Standard Finish	Natural Anodised
Other Finishes	Satin Black, Pearl White
Custom Finishes	Any Dulux / Interpon Powder Coat Colour
Mounting	Ceiling-to-Floor / Ceiling-to-Desk, Surface Mounted
Kit Includes	Divider, Escutcheon Plate, Internal Foot Plate

DIMENSIONS

Column cross-section: 100 x 100mm rectangular profile, 1 division	
WIDTH 100 mm	HEIGHT 100 mm
DIVISIONS 1	LENGTHS 3-6 m

KIT CONTENTS & KEY FEATURES

- Extruded aluminium column — strong, lightweight, corrosion resistant
- Complete kit: divider, escutcheon plate, internal foot plate included
- Single division suits one cable run or a compact single-outlet drop
- Natural Anodised standard finish — durable, low-maintenance surface
- Also available in Satin Black and Pearl White to match any fitout
- Custom powder coat / anodised colours available on request
- Fast, tool-minimal installation — free measure and quote available

AVAILABLE LENGTHS

PART NO.	LENGTH	NOTES
SP1001001D3MAN	3.0m	Standard ceiling height installs
SP1001001D4MAN	4.0m	Suits higher ceiling / raised floor combinations
SP1001001D6MAN	6.0m	Suits warehouse and high-bay ceiling heights



SP100100 SERIES SERVICE COLUMN — 100 X 100MM (NATURAL ANODISED) —
ORDERING, FINISHES & COMPLIANCE



SP100100 Service Column — 100 x 100mm, 1 Division (Natural Anodised)

SP100100-1DIV-ANODISED

FULL ORDERING INFORMATION

	DESCRIPTION	NOTES
SP1001001D3MAN	SP100100 Service Column 100 x 100mm x 3.0m, 1 Division (Natural Anodised)	3.0m length
SP1001001D4MAN	SP100100 Service Column 100 x 100mm x 4.0m, 1 Division (Natural Anodised)	4.0m length
SP1001001D6MAN	SP100100 Service Column 100 x 100mm x 6.0m, 1 Division (Natural Anodised)	6.0m length

AVAILABLE FINISHES

 Natural Anodised	 Satin Black	 Pearl White
--	---	--

Compliance & Installation: Cableaway service columns are manufactured from extruded aluminium and finished to AS/NZS standards for surface-mounted power and data distribution. Installation must be carried out by a licensed electrician where power circuits are involved, in accordance with AS/NZS 3000 Wiring Rules. Each column ships as a complete kit including top plate, escutcheon plate, internal foot plate, jacking bolt and divider; an optional Tee Bar mounting kit is available for column runs requiring intermediate ceiling support. Cableaway reserves the right to alter specifications without notice.

Custom finishes: in addition to the standard finishes shown, Cableaway can powder coat or anodise service column components to any Dulux or Interpon colour on request — visit dulux.com.au or interpon.com.au for the full colour range, or call 1300 883 452.