




SP32 SERIES ROUND SERVICE COLUMN — 32MM DIAMETER (SATIN BLACK)

SP32 Service Column — 32mm Diameter, 1 Division (Satin Black)

SP32-1DIV-SATINBLACK



Cableaway's SP32 service pole is manufactured from strong and lightweight extruded aluminium, providing an easy, attractive and economical way to distribute power and telecommunications cabling from an open ceiling space down to desk or workstation height. At 32mm diameter with 1 division, it suits a single cable run or compact single-outlet drop. Each pole ships as a complete kit — extruded column, Top Plate, Escutcheon Plate, Internal Foot Plate — ready to install without sourcing separate mounting hardware. Available in 3m, 4m and 6m standard lengths in Satin Black finish. Typical applications include office workstations, classrooms, retail outlets and factory floors.

TECHNICAL SPECIFICATIONS

Series Reference	SP32-1DIV-SATINBLACK
Column Diameter	32mm diameter
Divisions	1 (single cable channel)
Standard Lengths	3.0m, 4.0m, 6.0m
Body Material	Extruded Aluminium
Standard Finish	Satin Black
Other Finishes	Natural Anodised, Pearl White
Custom Finishes	Any Dulux / Interpon Powder Coat Colour
Mounting	Ceiling-to-Floor / Ceiling-to-Desk, Surface Mounted
Kit Includes	Top Plate, Escutcheon Plate, Internal Foot Plate

DIMENSIONS

Column cross-section: 32mm diameter, round profile, 1 division	
DIAMETER 32 mm	DIVISIONS 1
MIN LENGTH 3000 mm	MAX LENGTH 6000 mm

KIT CONTENTS & KEY FEATURES

- Extruded aluminium column — strong, lightweight, corrosion resistant
- Complete kit: top plate, escutcheon plate, internal foot plate included
- Single division suits one cable run or a compact single-outlet drop
- Satin Black standard finish — durable, low-maintenance surface
- Also available in Natural Anodised and Pearl White to match any fitout
- Custom powder coat / anodised colours available on request
- Fast, tool-minimal installation — free measure and quote available

AVAILABLE LENGTHS

PART NO.	LENGTH	NOTES
SP321D3MBLK	3.0m	Standard ceiling height installs
SP321D4MBLK	4.0m	Suits higher ceiling / raised floor combinations
SP321D6MBLK	6.0m	Suits warehouse and high-bay ceiling heights



SP32 SERIES ROUND SERVICE COLUMN — 32MM DIAMETER (SATIN BLACK) —
ORDERING, FINISHES & COMPLIANCE



SP32 Service Column — 32mm Diameter, 1 Division (Satin Black)

SP32-1DIV-SATINBLACK

FULL ORDERING INFORMATION

	DESCRIPTION	NOTES
SP321D3MBLK	SP32 Service Pole 32mm diameter x 3.0m, 1 Division (Satin Black)	3.0m length
SP321D4MBLK	SP32 Service Pole 32mm diameter x 4.0m, 1 Division (Satin Black)	4.0m length
SP321D6MBLK	SP32 Service Pole 32mm diameter x 6.0m, 1 Division (Satin Black)	6.0m length

AVAILABLE FINISHES

 Natural Anodised	 Pearl White	 Satin Black
--	---	--

Compliance & Installation: Cableaway service columns are manufactured from extruded aluminium and finished to AS/NZS standards for surface-mounted power and data distribution. Installation must be carried out by a licensed electrician where power circuits are involved, in accordance with AS/NZS 3000 Wiring Rules. Each column ships as a complete kit including top plate, escutcheon plate, internal foot plate, jacking bolt and divider; an optional Tee Bar mounting kit is available for column runs requiring intermediate ceiling support. Cableaway reserves the right to alter specifications without notice.

Custom finishes: in addition to the standard finishes shown, Cableaway can powder coat or anodise service column components to any Dulux or Interpon colour on request — visit dulux.com.au or interpon.com.au for the full colour range, or call 1300 883 452.