




SP7550 SERIES SERVICE COLUMN — 75 X 50MM (PEARL WHITE)

SP7550 Service Column — 75 x 50mm, 1 Division (Pearl White)

SP7550-1DIV-PEARLWHITE



Cableaway's SP7550 service column is manufactured from strong and lightweight extruded aluminium, providing an easy, attractive and economical way to distribute power and telecommunications cabling from an open ceiling space down to desk or workstation height. At 75 x 50mm with 1 division, it suits a single cable run or compact single-outlet drop. Each pole ships as a complete kit — extruded column, Top Plate, Escutcheon Plate, Internal Foot Plate, Jacking Bolt, Divider, Tee Bar Kit (optional) — ready to install without sourcing separate mounting hardware. Available in 3m, 4m and 6m standard lengths in Pearl White finish. Typical applications include office workstations, classrooms, retail outlets and factory floors.

TECHNICAL SPECIFICATIONS

Series Reference	SP7550-1DIV-PEARLWHITE
Column Size	75 x 50mm
Divisions	1 (single cable channel)
Standard Lengths	3.0m, 4.0m, 6.0m
Body Material	Extruded Aluminium
Standard Finish	Pearl White
Other Finishes	Natural Anodised, Satin Black
Custom Finishes	Any Dulux / Interpon Powder Coat Colour
Mounting	Ceiling-to-Floor / Ceiling-to-Desk, Surface Mounted
Kit Includes	Top Plate, Escutcheon Plate, Internal Foot Plate, Jacking Bolt, Divider, Tee Bar Kit (optional)

DIMENSIONS

Column cross-section: 75 x 50mm rectangular profile, 1 division	
WIDTH 75 mm	HEIGHT 50 mm
DIVISIONS 1	LENGTHS 3-6 m

KIT CONTENTS & KEY FEATURES

- Extruded aluminium column — strong, lightweight, corrosion resistant
- Complete kit: top plate, escutcheon plate, internal foot plate, jacking bolt, divider, tee bar kit (optional) included
- Jacking bolt allows fine height adjustment for a secure ceiling-to-floor fit
- Single division suits one cable run or a compact single-outlet drop
- Pearl White standard finish — durable, low-maintenance surface
- Also available in Natural Anodised and Satin Black to match any fitout
- Custom powder coat / anodised colours available on request
- Fast, tool-minimal installation — free measure and quote available
- Optional Tee Bar mounting kit available for intermediate ceiling support on longer runs

AVAILABLE LENGTHS

PART NO.	LENGTH	NOTES
SP75501D3MPW	3.0m	Standard ceiling height installs
SP75501D4MPW	4.0m	Suits higher ceiling / raised floor combinations
SP75501D6MAPW	6.0m	Suits warehouse and high-bay ceiling heights



SP7550 SERIES SERVICE COLUMN — 75 X 50MM (PEARL WHITE) — ORDERING, FINISHES & COMPLIANCE



SP7550 Service Column — 75 x 50mm, 1 Division (Pearl White)

SP7550-1DIV-PEARLWHITE

FULL ORDERING INFORMATION

	DESCRIPTION	NOTES
SP75501D3MPW	SP7550 Service Column 75 x 50mm x 3.0m, 1 Division (Pearl White)	3.0m length
SP75501D4MPW	SP7550 Service Column 75 x 50mm x 4.0m, 1 Division (Pearl White)	4.0m length
SP75501D6MAPW	SP7550 Service Column 75 x 50mm x 6.0m, 1 Division (Pearl White)	6.0m length

AVAILABLE FINISHES

 Natural Anodised	 Pearl White	 Satin Black
---	--	---

Compliance & Installation: Cableaway service columns are manufactured from extruded aluminium and finished to AS/NZS standards for surface-mounted power and data distribution. Installation must be carried out by a licensed electrician where power circuits are involved, in accordance with AS/NZS 3000 Wiring Rules. Each column ships as a complete kit including top plate, escutcheon plate, internal foot plate, jacking bolt and divider; an optional Tee Bar mounting kit is available for column runs requiring intermediate ceiling support. Cableaway reserves the right to alter specifications without notice.

Custom finishes: in addition to the standard finishes shown, Cableaway can powder coat or anodise service column components to any Dulux or Interpon colour on request — visit dulux.com.au or interpon.com.au for the full colour range, or call 1300 883 452.