



SD SERIES ALUMINIUM SKIRTING DUCT — 40 X 150MM 2-CHANNEL (NATURAL ANODISED)

40 x 150mm 2-Channel Aluminium Skirting Duct — Complete System (Natural Anodised)

SD40150-2CH-ANODISED




Cableaway's SD Series skirting duct is the easiest way to house and distribute power and data cabling, from large commercial fit-outs to the small home office. It mounts directly to the wall with no building modifications required, giving a clean, flexible cable management system for now and into the future. The 40 x 150mm duct is available in 2-channel configuration, separating power from data/AV cabling along a 2.4m extruded aluminium length. It handles Cat5, Cat6 and Cat6A data cabling, and — using Cableaway's 45 Series multimedia outlets — audio/visual connections including microphone, HDMI, VGA and component video. This datasheet covers the complete 40 x 150mm system in Natural Anodised: duct body, both lid options, and the full accessory range needed for a finished installation.

TECHNICAL SPECIFICATIONS

System Reference	SD40150-2CH-ANODISED
Duct Body Part No.	SD401502DA
Channels	2 (Power / Data separated)
Standard Length	2.4m
Body Material	Extruded Aluminium
Standard Finish	Natural Anodised
Other Finishes	Satin Black, Pearl White, Oyster Grey
Custom Finishes	Any Dulux / Interpon Powder Coat Colour
Mounting	Direct to Wall — Surface Mounted
Data Compatibility	Cat5 / Cat6 / Cat6A
AV Compatibility	45 Series Multimedia Outlets (HDMI, VGA, Audio, Component)

DUCT CROSS-SECTION



KEY FEATURES

- Extruded aluminium body — strong, lightweight, corrosion resistant
- 2-Channel design keeps power and data/AV cabling safely separated
- Surface wall-mounted — no chasing or building modification required
- Choice of Drop-In or Clip-On lid to suit installation preference
- Compatible with Cat5, Cat6 and Cat6A structured cabling
- Supports 45 Series multimedia outlets for AV connectivity
- Full accessory range: joiners, earthing kits, GPO/data shrouds, end caps, corners
- Standard finishes of Black, White, Grey and Natural Anodised, plus custom powder coat
- Fast, tool-minimal installation — free measure and quote available

LID OPTIONS

PART NO.	LID TYPE	NOTES
SDDL150A	Drop-In Lid	Lid drops into the duct body from above —flush tool-free fit - 1.2mtr
SDCL150A	Clip-On Lid	Lid clips over the duct body edges —secure snap-fit closure - 1.2 mtr



PRODUCT DATA SHEET

BETTER CABLE MANAGEMENT

1300 883 452

sales@cableaway.com.au

www.cableaway.com.au

SD SERIES ALUMINIUM SKIRTING DUCT — 40 X 150MM 2-CHANNEL (NATURAL ANODISED) — SYSTEM COMPONENTS & ACCESSORIES

40 x 150mm 2-Channel Aluminium Skirting Duct — Complete System (Natural Anodised)

SD40150-2CH-ANODISED

COMPLETE SYSTEM — BODY, LIDS & ACCESSORIES



SD401502DA

Duct Body (2 Channel) 2.4mtr

40 X 150mm X 2.4m 2 Channel Skirting Duct (natural Anodised) Duct Body Only



SDDL150A

Drop-In Lid Section 1.2mtr

40 X 150mm Drop In Lid Section (natural Anodised)



SDCL150A

Clip-On Lid Section 1.2mtr

40 X 150mm Clip On Lid Section (natural Anodised)



Joiner / Earth Kit

SDJK40

Alignment Joiner Kit

Alignment Joiner Kit Suits 40w Skirting Duct



SDCFC150A

Clip-On Front Cover 150mm

Clip On Front Cover To Suit 150h Skirting Duct Anodised



SDDFC150A

Drop-In Front Cover 150mm

Drop In Front Cover To Suit 150h Skirting Duct Anodised



SDPSK

GPO Shroud Kit


SD Series GPO Shroud Kit



SDDMK

Data / Voice Mount Kit

SD Series Data / Voice Mount Kit



Internal Earth Kit

SDIEK

Internal Butt Join Earthing Kit

Internal Butt Join Earthing Kit



SDCNR40150A

Corner Kit

Corner To Suit 40 X 150mm Skirting Duct Silver Powder Coat



SDBE40150A

Blank End

Blank End To Suit 40 x 150mm Skirting Duct Natural Anodised



SD SERIES ALUMINIUM SKIRTING DUCT — 40 X 150MM 2-CHANNEL (NATURAL ANODISED) — ORDERING, FINISHES & COMPLIANCE



40 x 150mm 2-Channel Aluminium Skirting Duct — Complete System (Natural Anodised)

SD40150-2CH-ANODISED

FULL ORDERING INFORMATION

	DESCRIPTION	NOTES
SD401502DA	Duct Body (2 Channel)	Per length — see specs
SDDL150A	Drop-In Lid Section	Per length — matches duct body
SDCL150A	Clip-On Lid Section	Per length — matches duct body
SDJK40	Alignment Joiner Kit	1 per duct joint
SDCFC150A	Clip-On Front Cover	As required
SDDFC150A	Drop-In Front Cover	As required
SDPSK	GPO Shroud Kit	1 per outlet location
SDDMK	Data / Voice Mount Kit	1 per outlet location
SDIEK	Internal Butt Join Earthing Kit	1 per duct joint
SDCNR40150A	Corner Kit	1 per external/internal corner
SDBE40150A	Blank End	2 per duct run

AVAILABLE FINISHES

 Satin Black	 Pearl White	 Oyster Grey	 Natural Anodised
---	--	---	---

Compliance & Installation: Cableaway SD Series skirting duct is manufactured from extruded aluminium and finished to AS/NZS standards for surface-mounted cable management. Installation must be carried out by a licensed electrician where power circuits are involved, in accordance with AS/NZS 3000 Wiring Rules. Earth continuity accessories (Internal Butt Join Earthing Kit) must be fitted at every joint to maintain earth continuity along the duct run where metallic duct is used for power reticulation. Cableaway reserves the right to alter specifications without notice.

Custom finishes: in addition to the standard finishes shown, Cableaway can powder coat skirting duct components to any Dulux or Interpon colour on request — visit dulux.com.au or interpon.com.au for the full colour range, or call 1300 883 452.